


SEMI-FINISHED CR-39 LENSES

RI 1.498

KRYPTOK 28 (KT28)

65 MM



PRODUCT RANGE

BASE (dpt)	True curve (dpt)	CONVEX RADIUS (mm)	RCC (dpt)	CT (mm)	ET (mm)
1.50	1.22	407.20	-6.25	8.00	14.00
4.50	4.35	114.50	-6.25	5.50	7.30
4.50 (High Add)	4.35	114.50	-6.25	8.70	10.50
6.25	5.95	83.68	-6.25	5.50	5.50
8.25	7.97	62.50	-4.25	8.00	3.50

POWER RANGE

BASE (dpt)	ADDITION (dpt)															
	0.75	1.00	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.50	5.00
1.50	*	*	*	*	*	*	*	*	*	*	*	*	*	*		
4.50	*	*	*	*	*	*	*	*	*	*						
4.50 (High Add)											*	*	*	*	*	*
6.25	*	*	*	*	*	*	*	*	*	*	*	*	*	*		
8.25	*	*	*	*	*	*	*	*	*	*	*	*	*	*		

**CT – CENTRE THICKNESS
ET – EDGE THICKNESS**

Prepared by	Approved by	Page 1 of 1
AMOL MANDREKAR	SURAJ AROLKAR	